## TVR SERIES

slew drives for solar trackers



**TVR160** 

TVR200-Z31

**TVR204** 

**TVR250** 

**TVR300** 

**TVR315** 













Ratio	65
Weight [Kg]	17,27
Nominal Torque [Nm]	600
Maximum Torque [Nm]	1200
Holding Torque [kNm]	6
Base-Center Distance [mm]	141,6

Ratio	40
Weight [Kg]	38,54
Nominal Torque [Nm]	7000
Maximum Torque [Nm]	9600
Holding Torque [kNm]	34
Base-Center Distance [mm]	190

Ratio	59
Weight [Kg]	45,41
Nominal Torque [Nm]	7000
Maximum Torque [Nm]	13500
Holding Torque [kNm]	40
Base-Center Distance [mm]	190

Ratio	50
Weight [Kg]	42,67
Nominal Torque [Nm]	10000
Maximum Torque [Nm]	13000
Holding Torque [kNm]	55
Base-Center Distance [mm]	217

Ratio	61
Weight [Kg]	51,44
Nominal Torque [Nm]	7000
Maximum Torque [Nm]	12000
Holding Torque [kNm]	55
Base-Center Distance [mm]	240

Ratio	63
Weight [Kg]	50,75
Nominal Torque [Nm]	7000
Maximum Torque [Nm]	20000
Holding Torque [kNm]	55
Base-Center Distance [mm]	247